## Rec'd PCT/PTO 22 DEC 2004

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

## (19) World Intellectual Property Organization

International Bureau



## 

(43) International Publication Date 15 January 2004 (15.01.2004)

**PCT** 

(10) International Publication Number WO 2004/006233 A1

(51) International Patent Classification7:

(21) International Application Number:

PCT/IB2003/002930

G11B 7/24

(22) International Filing Date:

13 June 2003 (13.06.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 02077656.3

4 July 2002 (04.07.2002) El


- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): LANKHORST, Martijn, H., R. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). VAN PIETERSON, Liesbeth

[NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). VAN SCHLJNDEL, Mark [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

- (74) Agent: DEGUELLE, Wilhelmus, H., G.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: REWRITALBE OPTICAL DATA STORAGE MEDIUM AND USE OF SUCH A MEDIUM



(57) Abstract: A rewritable optical data storage medium (20) for high-speed recording by means of a focused radiation beam (10) is described. The medium (20) comprises a substrate (1) carrying a stack (2) of layers. The stack (2) comprises a first dielectric layer (3), a second dielectric layer (5), and a recording layer (4) of a phase-change material of an alloy comprising Sb and Te. The recording layer (4) is interposed between the first dielectric layer (3) and the second dielectric layer (5). The alloy additionally contains 2 - 10 at.% of Ga, by which a significant improvement of the maximum data rate during direct overwrite is achieved. By furthermore adding 0.5 - 4.0 % of Ge to the alloy the archival life stability is enhanced.